

HYCON HPP18E FLEX POWER PACK



HIGH POWER EFFICIENCY

VARIABLE FLOW AND RPM REGULATION

COMPACT SIZE



PRODUCT FEATURES

HYCON HPP18E FLEX is equipped with a 13,2 kW (18 HP) motor, and the flow can be set to 20 - 30 - 40 - 46 lpm which make it the perfect power pack for professional and specialized companies within concrete cutting and coring.

On electric power packs of other brands, the oil flow adjusts by means of valves, and in this case, the oil often overheats from insufficient cooling.

HYDRAULIC POWER PACK HPP18E FLEX CUT

Item no.	2020211
Oil flow [LPM / GPM]	20 - 30 - 40 - 46 / 5 - 8 - 10 - 12
Working pressure [bar / psi]	120 / 1750
Max pressure [bar / psi]	160 / 2320
Hydraulic oil tank capacity [l / gal]	11 / 2.9
Electrical motor	Hoyer HMA3 132M2 (13.2 kW)
Electrical supply [V - Hz]	3 x 400 - 50 / 3 x 480 - 60
Ampere required [400V 50Hz / 480V 60Hz]	35 / 25
Dimensions L x W x H [mm / inch]	805 x 625 x 704 / 32 x 25 x 28
Weight [kg / lbs]	155 / 298
Sound power level L _{Wa} [dB]	99

THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS · CORE DRILLS · POST DRIVERS · PICK HAMMER · LIGHT & HEAVY DUTY BREAKERS
SUBMERSIBLE PUMPS · ROCK DRILLS · UNDERWATER EQUIPMENT · GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S
Juelstrupparken 11
DK-9530 Støvring

Tel.: +45 9647 5200
Mail: hycon@hycon.dk
www.hycon.dk

DISTRIBUTOR: